

Electric Thermostatic Air Drying Oven

○ Main Application

- It is used for drying, baking, melting wax and sterilizing in the laboratory of mineral enterprises.

○ Product Produce

- The box is made of mirror stainless steel by argon arc welding, and the outside of the box is made of high quality steel plate.
- Adopt microcomputer P.I.D. temperature controller with overtemperature deviation protection digital display, with timing function, accurate and reliable temperature control.
- The hot air circulation system is composed of a fan that can run continuously at high temperature and suitable air duct to improve the temperature uniformity in the working room.
- Using the new synthetic silicon seal strip, can operate at high temperature for a long time, long service life, easy to replace.
- Temperature Control: Constant temperature fluctuation is $\pm 1^{\circ}\text{C}$, Temperature accuracy is 0.1°C .
- Timing Range: 1-9999min;
- Power: AC 220V \pm 10% 50HZ
- Optional: Independent temperature limit alarm system will automatically stop when the temperature exceeds the limit to ensure the safe operation of the experiment without accidents.



XCH-9420A



Internal stainless steel

Name	Model	TEMP Range (°C)	Capacity (L)	INTR DIM(mm) W×D×H	EXT DIM(mm) W×D×H	Power (kW)	Shelf (Standard)	Remark
Electric Thermostatic Air Drying Oven	XCH-9070A	RT+10 ~ 250	70	450×400×450	740×618×630	1.0	2	Use within 220°C
	XCH-9140A	RT+10 ~ 250	140	550×450×550	840×670×730	1.5	2	
	XCH-9240A	RT+10 ~ 250	240	600×500×750	880×720×930	2.5	2	
	XCH-9420A	RT+10 ~ 250	420	640×585×1355	780×750×1880	3.1	3	
	XCH-9620A	RT+10 ~ 250	620	780×600×1355	980×800×1880	4.0	4	
	XCH-9920A	RT+10 ~ 250	1000	1000×600×1600	1140×800×2150	5.2	4	
Electric Thermostatic Air Drying Oven	XCH-9075A	RT+10 ~ 300	70	450×400×450	740×618×630	1.0	2	Use within 270°C
	XCH-9145A	RT+10 ~ 300	140	550×450×550	840×670×730	1.5	2	
	XCH-9245A	RT+10 ~ 300	240	600×500×750	880×720×930	2.5	2	
	XCH-9425A	RT+10 ~ 300	420	640×585×1355	780×750×1880	3.1	3	
	XCH-9625A	RT+10 ~ 300	620	780×600×1355	980×800×1880	4.0	4	
	XCH-9925A	RT+10 ~ 300	1000	1000×600×1600	1140×800×2150	5.2	4	